



**S.A. CASH
REGISTERS**



955 PORT ROAD
CHELTHENHAM 5014

8347 3777

SAMSUNG DIGITall
everyone's invited™

Dot type Receipt Printer



- Fast Printing Speed
- USB Interface
- Compact size



Dot receipt printer SRP270


Chic White

Dark Grey

SRP-270

Dot receipt printer

World best receipt printer SRP-270 features the fastest printing speed, high durability. Specially SRP-270 is very suitable for the store manager to save running cost considerably and to purchase the receipt printer at low price. SRP-270 has the solution such as competitor's compatibility and multiple driver at any OS environment.



SRP-270

DOT RECEIPT PRINTER

SRP-270 Series Model



SRP-270A



SRP-270C



SRP-270D



Paper Jam & Skew Free technology

Feature

- Fastest printing speed in the world (4.6LPS)
- Multiple interface in modular type
*SRP-270's interface board is available for our SRP-350's in common use.
- High durability (18M Lines)
- Complete compatibility
- Compact design
- Easy-to-use
 - Plug & play
 - Auto paper loading for paper replacement

Specifications

MODEL		SRP-270
Print	Printing Method	9 pin serial dot matrix
	Printing Speed	4.6LPS(40 Columns), 8.4 LPS (16 Columns)
	Printing Direction	Bidirectional printing
	Character per line	Font A: 40 / 42 Font B: 33 / 35
	Character Size	Font A: 1.2(W) x 3.1(H) Font B: 1.6(W) x 3.1(H)
Paper	Paper Type	Plain Paper
	Paper Width	76.0 ± 0.5mm
	Paper Roll Diameter	Max. ø 83.0mm
Reliability	MCBF	18,000,000 Lines
Character Set		Alphanumeric Character: 95 Extended Graphic: 128 x 8 page International character: 32
Emulation		TM-U200, TM-U300, IDP-3410
Driver		Windows 95/98/2000/NT
Sensor		Paper end sensor Near end sensor (option)
Drawer Port		1port (Max.2 drawer)
Inter face		RS-232C(Standard), RS-485, USB, IEEE-1284
Power Supply (Adapter)		AC 120V - 230V
Dimension (W x L x H mm)	SRP-270A	160mm x 247mm x 130mm
	SRP-270C	160mm x 247mm x 149mm
	SRP-270D	160mm x 294mm x 159mm



- ① Interface Connector
- ② Drawer Port
- ③ Power Connector



- ① RS-232C
- ② RS-485
- ③ USB
- ④ IEEE-1284

Multiple Interface Board



HEAD OFFICE (SEOUL, KOREA)

6th FL, Samsung Main Bldg.
250, 2-Ka, Teopyeong-Ro, Choong-Ku, Seoul, Korea
Tel: +82-2-751-2788, 2787 Fax: +82-2-751-2680
<http://www.samsungprinter.com>

*Design and specifications are subject to change without notice.



**S.A. CASH
REGISTERS**



955 PORT ROAD
CHELTHENHAM 5014

8347 3777

SRP270



COMPARISON

Item	SRP-250(SAMSUNG)	SRP-270(SAMSUNG)	TM-U200(EPSON)
Print Method	Serial Dot Matrix	Serial Dot Matrix	Serial Dot Matrix
Print Speed	3.5(6.4) LPS	4.6(8.4) LPS	3.5(6.4) LPS
Paper Width	76mm	76mm	76mm
Print Columns	40 / 42	40 / 42	40 / 42
Reliability	Mecha	18M Lines	18M Lines
	Head	75M Chars	150M Chars
Interface	RS-232C, IEEE-1284	RS-232C, RS-485 USB, IEEE-1284	RS-232C, RS-485 IEEE-1284
Ribbon	Black	3M Chars	3M Chars
	Purple/Red	0.8M Chars	4M Chars
Dimension(W*L*Hmm)	177 * 277 * 140	160 * 248 * 130	160 * 248 * 133
Drawer Port	2	2	2